

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 235 197 A1

(12)

EUROPEAN PATENT APPLICATION

published in accordance with Art. 158(3) EPC

(43) Date of publication:
28.08.2002 Bulletin 2002/35

(51) Int Cl.7: **G09F 9/00**, G09F 9/30,
G01D 7/00, G01D 13/00,
B60K 35/00

(21) Application number: 01945776.1

(22) Date of filing: 02.07.2001

(86) International application number:
PCT/JP01/05736

(87) International publication number:
WO 02/009073 (31.01.2002 Gazette 2002/05)

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

(30) Priority: 24.07.2000 JP 2000221568
27.02.2001 JP 2001052563

(71) Applicant: NIPPON SEIKI CO., LTD.
Nagaoka-shi, Niigata 940-8580 (JP)

(72) Inventors:
• KOJIMA, Tetsuaki, c/o R & D Center
Nagaoka-shi, Niigata 940-2141 (JP)
• NAGANO, Kelichi, c/o R & D Center
Nagaoka-shi, Niigata 940-2141 (JP)


• SHIMA, Osamu, c/o R & D Center
Nagaoka-shi, Niigata 940-2141 (JP)
• ITAGAKI, Masao, c/o R & D Center
Nagaoka-shi, Niigata 940-2141 (JP)
• KOBAYASHI, Mitsugu, c/o R & D Center
Nagaoka-shi, Niigata 940-2141 (JP)
• UMEZAWA, Yukio, c/o R & D Center
Nagaoka-shi, Niigata 940-2141 (JP)

(74) Representative: Jackson, Richard Eric et al
Carpmaels & Ransford,
43 Bloomsbury Square
London WC1A 2RA (GB)

(54) DISPLAY ELEMENT AND DISPLAY DEVICE USING DISPLAY ELEMENT

(57) A display device includes a pointer 18 including an indicating part 18a, pointer driving unit 20 for rotating the pointer 18, and a display element 17 including an index part 23 indicated by the indicating part 18a. The display element 17 includes a pair of translucent substrates 26 and 27, stripe-shaped transparent electrode films 24 and 25 respectively formed on the translucent substrates 26 and 27, and light shielding parts 33 and 46 provided on at least one of the translucent substrates 26 and 27, and the index part 23 is made of an opening of the light shielding parts 33 and 46. The display element 17 includes a hole part 36 formed in a place corresponding to a rotation shaft of the pointer driving unit 20.

FIG. 1



BEST AVAILABLE COPY

Description

TECHNICAL FIELD

[0001] The present invention relates to a dot matrix type display element and a display device using the dot matrix type display element.

BACKGROUND ART

[0002] Hitherto, there is a dot matrix type liquid crystal display element 1 as shown in Fig. 13. The liquid crystal display element 1 includes a number of pixels 2 provided in a matrix form. As shown in Fig. 14, the liquid crystal display element 1 is such that polarizing plates 9 and 10 are bonded to both surfaces of a liquid crystal cell 8 in which a liquid crystal 7 is sealed between a pair of translucent substrates 5 and 6 provided with transparent electrode films 3 and 4. The respective transparent electrode films 3 and 4 are formed into such a stripe shape that they are orthogonal to each other, and portions where the transparent electrode films 3 are opposite to the transparent electrode films 4 become the pixels 2. The liquid crystal display element 1 can display various figures and characters (including numerals) by switching on/off the respective pixels 2.

[0003] However, since the contour of a displayed figure or character becomes sawtooth, there has been a problem that the figure or the character is disfigured. That is, since the shape of each of the pixels 2 is square, in the case where the contour of the figure or the character, which is displayed by selectively switching on/off the pixels 2, is an oblique line or a curved line, the figure or the character becomes sawtooth.

[0004] The present invention has been made in view of the problem, and provides a display device which can display a character and a figure having an unsawtooth contour.

DISCLOSURE OF THE INVENTION

[0005] A display device includes a pointer including an indicating part, pointer driving means for rotating the pointer, and a display element including an index part indicated by the indicating part. The display element includes a pair of translucent substrates, stripe-shaped transparent electrode films respectively formed on the translucent substrates, and a light shielding part provided on at least one of the translucent substrates. The index part is made of an opening of the light shielding part. The display element includes a hole part formed in a place corresponding to a rotation shaft of the pointer driving means.

[0006] Alternatively, a display device includes a pointer including an indicating part, pointer driving means for rotating the pointer, a first display plate including a fixed display part indicated by the indicating part, and a second display plate made of a dot matrix type display ele-

ment and disposed in front of or behind the first display plate. The first display plate and the second display plate respectively include hole parts formed in places corresponding to a rotation shaft of the pointer driving means.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007]

Figs. 1 to 5 are views showing a first embodiment, in which Fig. 1 is a front view of a liquid crystal display element, Fig. 2 is a front view of a display device, Fig. 3 is a sectional view of the display device, Fig. 4 is a sectional view showing the liquid crystal display element, and Fig. 5 is a primary part enlarged view of the liquid crystal display element.

Fig. 6 is a primary part enlarged view of a liquid crystal display element, showing a second embodiment. Figs. 7 to 10 are views showing a third embodiment, in which Fig. 7 is a sectional view of a display device, Fig. 8 is a perspective view of a display plate and a liquid crystal display element, Fig. 9 is a sectional view of the display plate and the liquid crystal display element, and Fig. 10 is a primary part enlarged view of the display plate.

Fig. 11 is a primary part enlarged view of a display plate, showing a fourth embodiment.

Fig. 12 is a perspective view of a display plate and a liquid crystal display element, showing a fifth embodiment.

Figs. 13 and 14 are views showing the prior art, in which Fig. 13 is a front view of a liquid crystal display element, and Fig. 14 is a sectional view of the liquid crystal display element.

BEST MODE FOR CARRYING OUT THE INVENTION

[0008] Hereinafter, embodiments in which the present invention is applied to an on-vehicle display device, will be described with reference to the accompanying drawings. Figs. 1 to 5 are views showing a first embodiment.

[0009] Reference numeral 11 designates a housing, and this housing 11 includes a facing member 12 and a case body 13. The housing 11 contains three indicating instruments, that is, a speed indicator 14, a fuel indicator 15, and a water temperature indicator 16. The speed indicator 14 is larger than the fuel indicator 15 and the water temperature indicator 16, and is disposed between the fuel indicator 15 and the water temperature indicator 16.

[0010] The speed indicator 14 includes a liquid crystal display element 17, a pointer 18, a lightguide member 19, and a stepping motor 20 (pointer driving means). The pointer 18 is rotated by the stepping motor 20, and indicates an index part 23 (fixed display part) of the liquid crystal display element 17.

[0011] Reference numeral 21 designates a circuit board, and the stepping motor 20 is mounted on this cir-

cuit board 21. Reference numeral 22 designates a bulb (light emitting element), and this bulb 22 is connected to the circuit board 21. The liquid crystal display element 17 is illuminated through transmission of the light of the bulb 22. The light of the bulb 22 is guided by the light-guide member 19 to the pointer 18, and an indicating part 18a of the pointer 18 becomes luminous.

[0012] The liquid crystal display element 17 is such that polarizing plates 30 and 31 are bonded to both surfaces of a liquid crystal cell 29 in which a liquid crystal 28 is sealed between a pair of translucent substrates 26 and 27 on which transparent electrode films 24 and 25 are formed (refer to Fig.4). The respective transparent electrode films 24 and 25 are formed into such a stripe shape that they are orthogonal to each other, and places where the transparent electrode films 24 are opposite to the transparent electrode films 25 become pixels 32. Reference numeral 33 designates a light shielding layer (light shielding part), and openings of this light shielding layer 33 are fixed display parts (index parts 23 and numerals 34). A hole part 36 through which a rotation shaft 35 of the stepping motor 20 passes is formed in the liquid crystal display element 17.

[0013] The fuel indicator 15 and the water temperature indicator 16 respectively include character plates 37 and 38 and pointers 39 and 40. The character plates 37 and 38 are respectively such that black printing is applied to substrates made of translucent resin (for example, polycarbonate) except for index parts 41 and 42. The pointers 39 and 40 are rotated by stepping motors (not shown), and indicate the index parts 41 and 42 of the character plates 37 and 38.

[0014] Reference numeral 43 designates a protection cover, and this protection cover 43 is fixed to the facing member 12 by a fixing pawl. In the facing member 12, circular openings 12a, 12b and 12c are respectively formed in the places corresponding to the liquid crystal display element 17, and the character plates 37 and 38.

[0015] The liquid crystal display element 17 is of a negative display type in which the pixel 32 applied with a voltage is brought into a transmission state, and the pixel 32 applied no voltage is in a light shielding state. The liquid crystal display element 17 includes a variable display part 44 made of a region where the light shielding layer 33 is not provided, and this variable display part 44 displays alarm information such as a battery voltage shortage (see Fig. 2). Besides, as shown in Fig. 5, in order to bring the fixed display portions 23 and 34 into the transmission state, rectangular regions 45 and 46 wider than the fixed display portions 23 and 34 are brought into the transmission state.

[0016] Fig. 6 is a view showing a second embodiment. The second embodiment is different from the first embodiment only in a range in which a light shielding layer 46 is provided, and the other structure is the same as the first embodiment.

[0017] The light shielding layer 46 is provided around each of the fixed display parts 23 and 34 to have a pre-

determined width W and a frame shape. The predetermined width W of the light shielding layer 46 is larger than a diagonal length L of a pixel 32. In the liquid crystal display element 17, in order to bring the fixed display parts 23 and 34 into the transmission state, regions 47 respectively wider than the fixed display parts 23 and 34 and narrower than the light shielding layers 46 are brought into the transmission state.

[0018] According to the first embodiment or the second embodiment, the fixed display parts 23 and 34 and the variable display part 44 can be provided on one display element (the liquid crystal display element 17), and the contours of the fixed display parts 23 and 34 are formed of the openings of the light shielding layer 33, so that the contours of the fixed display parts 23 and 34 do not become sawtooth. Incidentally, although the light shielding layer 33 of the respective embodiments is laminated on the transparent electrode 24, for example, it may be formed on the front side surface of the translucent substrate 26 or may be formed on the front side surface of the polarizing plate 30.

[0019] Figs. 7 to 10 are views showing a third embodiment. The third embodiment is different from the first embodiment only in a polarizing plate 50 and a liquid crystal display element 51, and the other structure is similar to the first embodiment, and accordingly, the same symbols are given to the same portions as those of the first embodiment, and the explanation is omitted.

[0020] The display plate 50 is such that a light shielding part 53 is formed by printing on the front surface of a substrate 52 made of translucent resin (for example, polycarbonate). The light shielding part 53 is substantially arc-shaped when viewed from the front of the display plate 50. Openings are provided in the light shielding part 53, and the openings are index parts 54 and characters 55.

[0021] The liquid crystal display element 51 is such that polarizing plates 30 and 31 are bonded to both surfaces of a liquid crystal cell 56 in which a liquid crystal 28 is sealed between a pair of translucent substrates 26 and 27 on which transparent electrode films 24 and 25 are formed. The respective transparent electrode films 24 and 25 are formed into such a stripe shape that they are orthogonal to each other, and places where the transparent electrode films 24 are opposite to the transparent electrode films 25 become pixels 58.

[0022] Hole parts 59 and 60 through which a rotation shaft 35 of a stepping motor 20 passes are respectively formed in the display plate 50 and the liquid crystal display element 51.

[0023] The liquid crystal display element 50 is of a negative display type in which a figure or a character to be displayed is brought into a transmission state, and for example, display alarm information such as a battery voltage shortage is displayed. Besides, as shown in Fig. 10, in order to make light pass through the index part 54 and the character 55 of the display plate 50, rectangular regions 61 and 62 wider than the index part 54 and the

character 55 are brought into the transmission state.

[0024] Fig. 11 is a view showing a fourth embodiment. The fourth embodiment is different from the third embodiment only in a range in which a light shielding part 64 is provided, and the other structure is similar to the third embodiment.

[0025] The light shielding part 64 is provided around each of the index part 54 and the character 55 to have a predetermined width W and a frame shape. The predetermined width W of the light shielding part 64 is larger than a diagonal length L of the pixel 58. In the liquid crystal display element 51, in order to make light pass through the index part 54 and the character 55 of the display part 50, a region 65 wider than the index part 54 and the character 55 and narrower than an outer line of the light shielding part 64 is brought into the transmission state.

[0026] Fig. 12 is a view showing a fifth embodiment. The fifth embodiment is different from the third embodiment only in a display plate 66, and the other structure is similar to the third embodiment.

[0027] The display plate 66 is such that an index part 67 and a character 68 made of a colored layer are formed by printing on a substrate 69. A hole part 70 through which a rotation shaft 35 of a stepping motor 20 passes is formed in the display plate 66.

[0028] According to the third to fifth embodiments, the fixed display parts (the index parts 54 and 67, the characters 55 and 68) and the variable display part of the liquid crystal display element 51 can be provided in the speed indicator 14, and the contours of the fixed display parts do not become sawtooth. Incidentally, although the liquid crystal display element 51 of the third to fifth embodiments is disposed behind the polarizing plate 50 or 66, the liquid crystal display element 51 may be disposed in front of the polarizing plate 50 or 66, and the same operation and effect can be obtained.

[0029] Besides, in the first to fifth embodiments, although the pointer driving means is the stepping motor 20, for example, it may be a crossed coil type movement. Besides, although the light emitting element is the bulb 22, for example, it may be a light emitting diode. Besides, although the display element is the liquid crystal display element 17 or 51, for example, it may be an organic EL display element.

POSSIBILITY OF INDUSTRIAL APPLICATION

[0030] The present invention can be applied to a display device, and is particularly suitable for an on-vehicle display device.

Claims

1. A dot matrix type display element comprising:

a pair of translucent substrates;

stripe-shaped transparent electrode films respectively formed on the translucent substrates; and
a light shielding part formed on at least one of the translucent substrates,

characterized in that the display element comprises:

a variable display part made of a region where the light shielding part is not provided; and
a fixed display part made of an opening of the light shielding part.

2. A display element according to claim 1, **characterized in that** the light shielding part is provided around the opening to have a predetermined width.

3. A display element according to claim 2, **characterized in that** the predetermined width is larger than a diagonal length of a pixel.

4. A display device comprising:

a pointer including an indicating part;
pointer driving means for rotating the pointer; and
a display element including an index part indicated by the indicating part,

characterized in that

the display element comprises a pair of translucent substrates, stripe-shaped transparent electrode films respectively formed on the translucent substrates, and a light shielding part provided on at least one of the translucent substrates, and
the index part is made of an opening of the light shielding part.

5. A display device according to claim 4, **characterized in that** the display element includes a hole part formed in a place corresponding to a rotation shaft of the pointer driving means.

6. A display device according to claim 4, **characterized in that** a light emitting element for illuminating the display element from behind is provided.

7. A display device **characterized by** comprising:

a first display plate including a fixed display part; and
a second display plate made of a dot matrix type display element and disposed in front of or behind the first display plate.

8. A display device **characterized by** comprising:

a pointer including an indicating part;
pointer driving means for rotating the pointer;
a first display plate including a fixed display part
indicated by the indicating part; and
a second display plate made of a dot matrix
type display element and disposed in front of or
behind the first display plate. 5

9. A display device according to claim 8, **character-
ized in that** the first display plate and the second 10
display plate respectively include hole parts formed
in places corresponding to a rotation shaft of the
pointer driving means.
10. A display device according to claim 8, **character- 15
ized in that** the fixed display part is made of an
opening of a light shielding part, and the light shield-
ing part is provided around the fixed display plate
to have a predetermined width. 20
11. A display device according to claim 10, **character-
ized in that** the predetermined width is larger than
a diagonal length of a pixel of the second display
plate. 25
12. A display device according to any one of claims 8,
characterized in that a light emitting element for
illuminating the second display plate is provided. 30

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11




FIG. 12




FIG. 13
(PRIOR ART)





FIG. 14
(PRIOR ART)



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP01/05736

A. CLASSIFICATION OF SUBJECT MATTER

Int.Cl⁷ G09F 9/00, G09F 9/30, G01D 7/00, G01D13/00, B60K35/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Int.Cl⁷ G09F 9/00, G09F 9/30, G01D 7/00, G01D13/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Jitsuyo Shinan Koho	1926-1996	Toroku Jitsuyo Shinan Koho	1994-2001
Kokai Jitsuyo Shinan Koho	1971-2001	Jitsuyo Shinan Toroku Koho	1996-2001

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	Microfilm of the specification and drawings annexed to the request of Japanese Utility Model Application No. 105584/1989 (Laid-open No. 44624/1991), (Kanto Seiki K.K.), 25 April, 1991 (25.04.91) (Family: none)	1-12
Y	JP 2-166420 A (Seiko Epson Corporation), 27 June, 1990 (27.06.90) (Family: none)	1-12
Y	JP 2000-111674 A (Citizen Watch Co., Ltd.), 21 April, 2000 (21.04.00) (Family: none)	5, 6, 9-12
Y	JP 58-176677 A (Hitachi, Ltd.), 17 October, 1983 (17.10.83) (Family: none)	7

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search
27 July, 2001 (27.07.01)Date of mailing of the international search report
07 August, 2001 (07.08.01)Name and mailing address of the ISA/
Japanese Patent Office

Authorized officer

Facsimile No.

Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)